



[Catalog Home](#)

Product Datasheet

CHANCE

M3H67B -- M3 Switch



25 kV, 125kV, 600 A, Single-Phase Hookstick Disconnect Switch

Product Specifications

Overhead Product	Single Phase - Distribution Disconnect Switch (Crossarm Mounted)
Voltage(BIL)	25kV (125kV)
Rated Current	600 A
Insulator Type	ESP™ Polymer (2 1/4" Bolt Circle)
Base Type	Distribution Base, Smooth Slots
Carriage Bolt Length	8" (203 mm)
Captive Hardware	No
Terminal Connectors (ATC 1343)	No
Open Position Latch (160° Opening)	No
Bypass Studs	No
Nominal Voltage	25 kV
Maximum System Voltage	27kV
BIL (LIW)	125kV
Rated 60 Htz Withstand; Dry (Wet)	50kV (45kV)
Continuous Current Rating	630 A
8hr Emergency Overload	1080 A
Momentary Current Rating	40kA, asymmetrical
Short Time Withstand Current (2 sec)	25kA, symmetrical
Short Time Withstand Current (3 sec)	16kA, symmetrical
Maximum Temperature Rise @ 600A	28°C
Insulator Color	Dark Gray
Leakage Distance (Insulator)	21.9" (556.3mm)
Dry Arcing Distance (Insulator)	21.9" (556.3mm)
Cantilever (Insulator)	8.1" (205.7mm)
Tension (Insulator)	1,000 Lbs (4.45kN)
Torsion (Insulator)	5000 Lbs (22.24kN)

Compression (Insulator)	3,000 in Lbs (339 N-M)
Base Material	Galvanized Steel per ASTM A153
Base Description	Distribution Base, Smooth Slots with four 1/2" Carriage Bolts and backstrap
Dead-ending (Working Load)	8,000 Lbs
Blade(s)	Solid Copper (two blade truss-member)
Hinge(s)	Silver / Silver
Contact(s)	Silver / Silver
Terminal Pads	NEMA two-hole, Tin-plated Copper
Governing Standards	All Applicable ANSI/IEEE Standards
Drawing	Click HERE to view drawing of switch
Crated Weight	38.71 lbs
Material Type	Non-Standard
UPC Code	09635932141
Standard Package	1
Standard Package Unit	Each
Min Order Qty	1
Weight / Ea.	38.71 lbs

Compressed Product Number

M3H67B

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.