

# Product data sheet

## Characteristics

# 2510KW2

## Manual Switch - NEMA 4 - 3P - Toggle Operated - No Indicator - 600VAC

Product availability : Stock - Normally stocked in distribution facility



Price\* : 397.71 USD



### Main

Product or component type	Single Unit Manual Switch
Range of product	K

### Complementary

Line Rated Current	30 A
Cable entry	0.75 NPT (bottom)
Motor power hp	2 hp at 115 V AC 1 hp at 90 V DC 2 hp at 115 V DC 1.5 hp at 230 V DC 7.5 hp at 230 V AC 10 hp at 460 V AC 10 hp at 575 V AC
System Voltage	600 V AC 230 V DC
Poles description	3P
Control type	Toggle
Phase	3 phases
Local signalling	No indicator
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
AWG gauge	AWG 14...AWG 10 (copper)
Height	4.38 in
Width	3 in
Depth	4.25 in

### Environment

Product certifications	UL listed file E42243 CCN NLRV
------------------------	--------------------------------

Sep 06, 2017

CSA LR25490 class 3211 05  
CE

---

NEMA degree of protection	NEMA 4 die cast zinc alloy standard size
---------------------------	--

---

### Ordering and shipping details

---

Category	21102 - 2510,2511,2512 K
Discount Schedule	CP1
GTIN	00785901077053
Nbr. of units in pkg.	1
Package weight(Lbs)	2.9500000000000002
Returnability	Y
Country of origin	MX

---

### Offer Sustainability

---

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---