



# Compression Splice Full Tension

by FARGO  
Catalog ID: 811222

Compression Splice, Static Wire, Full Tension, for EHS Steel,  
Alumoweld(R), Dia. Range 0.306-0.313



\* Representative image

## Product Details

### General

Compression Method	Single Die
Material	Aluminum Alloy
Press Minimum	60 to
Tension Range	0 lb
UPC	096359251613

### Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	8 in
Weight	0.294 lb

### Conductor Related

Conductor Diameter (Main) - Maximum	0 in
Conductor Diameter (Main) - Minimum	0 in
Conductor Diameter - Maximum	0.313 in
Conductor Diameter - Minimum	0.306 in
Conductor Diameter Range	0.306 - 0.313
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

### Certifications and Compliance

UL Listed	No
-----------	----

For further technical assistance, please contact us

#### Domestic Customer Service

Hubbell Power Systems  
210 N. Allen Centralia, MO 65240 USA  
Phone: (573) 682-5521  
Fax: (573) 682-8475  
Email: [hpscsc@hubbell.com](mailto:hpscsc@hubbell.com)

#### International Customer Service

Phone: +1-573-682-5521  
Fax: +1-573-682-8516  
Email: [hpsintlcs@hubbell.com](mailto:hpsintlcs@hubbell.com)