



BURNDY Catalog Number

UPC Number

Description

Status

KA4CRK

7818103598911

KA-LUG POS Qty1=5pcs

Active

Web Use

BURNDY Product Line

Dimensional

Length (in)	1.11
Thickness (in)	1/10
Height (in)	0.77
B Length (Fraction)	8/17
Size (Hex) or Size (Bolt)	5/16
Stud Size (in)	1/4
Thickness	0.10
Size (Hex) or Size (Bolt) - in	0.31
B Length (in)	0.47
Pad Width (in)	0.54
N (in)	0.25
Hole Size (in)	0.28
Height (Fraction) (in)	67/87

General

Product Description

Copper Alloy Terminal, Bolt Size:
5/16 IN, Conductor Range
(Main/Primary): 14 - 4
AWG, Installation Torque: 45 IN-LB

Conductor(s)

Copper Solid Size (Range)	14 AWG-4 AWG
Copper Stranded (Range)	14 AWG-4 AWG

Physical

Screw Type	Slot
Type of Hardware	5/16 UNF Hex SetScrew
Installation Torque	45
Type of Plating	Unplated
Plated (Yes or No)	N
Product Material	Copper

Approvals / Certifications

UL Recognized	N
UL Listed	N
CSA Certified	N
ROHS Compatible	Compliant
CULUS	Y
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175