



BURNDY Catalog Number
UPC Number
Description
Status

KA8CRK
 7818103599144
 KA-LUG POS Qty1=5pcs
 Active

Web Use
 BURNDY Product Line

Dimensional

| | |
|---------------------------|-------|
| Length (in) | 0.81 |
| Thickness (in) | 2/25 |
| Height (in) | 0.61 |
| B Length (Fraction) | 8/25 |
| Size (Hex) or Size (Bolt) | 7/32 |
| Stud Size (in) | #10 |
| Thickness | 0.08 |
| B Length (in) | 0.32 |
| Pad Width (in) | 0.38 |
| N (in) | 0.19 |
| Hole Size (in) | 0.21 |
| Height (Fraction) (in) | 36/59 |

General

| | |
|---------------------|---|
| Product Description | Copper Alloy Terminal, Bolt Size: 7/32 IN, Conductor Range (Main/Primary): 14 AWG Solid - 8 AWG Stranded, Installation Torque: 25 IN-LB |
|---------------------|---|

Conductor(s)

| | |
|---------------------------|--------------|
| Copper Solid Size (Range) | 14 AWG-8 AWG |
| Copper Stranded (Range) | 14 AWG-8 AWG |

Physical

| | |
|---------------------|--------------------------|
| Screw Type | Slot |
| Type of Hardware | #12 UNC Slotted SetScrew |
| Installation Torque | 25 |
| Type of Plating | Unplated |
| Plated (Yes or No) | N |
| Product Material | Copper |

Approvals / Certifications

| | |
|--------------------|-------------|
| UL Recognized | N |
| UL Listed | N |
| CSA Certified | N |
| ROHS Compatible | Compliant |
| CULUS | Y |
| Industry Standards | UL468A-468B |

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175