



BURNDY Catalog Number
UPC Number

Description

Status

Web Use

BURNDY Product Line

KA25URK

7818103598533

Univ Term POS Qty1=2pcs, 14-1/0

Str.

Active

Dimensional

Width (in)	0.63
Length (in)	1.50
Bolt Hole Size (in)	0.25
Thickness	0.19
D - in	0.81
Pad Width (in)	0.63
N (in)	0.44

General

Number of Holes	1
Product Description	High strength aluminum alloy Universal Terminal, Wire Range:14 AWG-1/0 ,Torque:50 in lb,Stud Hole Size:1/4

Conductor(s)

Aluminum Size (Range)	8 AWG-1/0 AWG
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	14 AWG-1/0

Physical

Installation Torque	50
Type of Plating	Tin
Bolt Hole Size	1/4
Plated (Yes or No)	Y
Product Material	Aluminum

Approvals / Certifications

Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175