



BURNDY Catalog Number
UPC Number
Description
Status

KPA4CUPRK
 7818103599522
 Scrulug POS Qty1=3pcs
 Active

Web Use
 BURNDY Product Line

Dimensional	
Length (in)	1.28
Thickness (in)	4/57
Height (in)	1.00
Stud Size (in)	1/4
Thickness	0.07
D - in	0.71
Pad Width (in)	0.50
N (in)	0.33
Strip Length	9/16
General	
Number of Holes	1
Number of Screws	1
Product Description	Copper Alloy SCRULUG Terminal, Number Of Mounting Holes: 1, Conductor Range (Main/Primary): 14 AWG Solid - 4 AWG Stranded, Torque, 45 IN-LB
Conductor(s)	
Copper Solid Size (Range)	14 AWG-4 AWG
Copper Stranded (Range)	14 AWG-4 AWG
Physical	
Screw Type	Slot
Type of Hardware	5/16 Dia. Slot Robertson
Installation Torque	45
Type of Plating	Unplated
Plated (Yes or No)	N
Product Material	Copper
Approvals / Certifications	
UL Listed	N
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175