



KS90RK

by Burndy
Catalog ID: KS90RK

Prop 65 Notice

High copper alloy Split Bolt, SERVIT,Torque:80 in-lb,.

Features: UL467 Listed For Direct Burial Applications In Earth Or Concrete, Compact, High-Strength, High Copper Alloy SERVIT Split-Bolt Has Free-Running Threads And Easy To Grip Wrench Flats, Highly Resistant To Cracking And Corrosion, Length: 0.85 IN, Installation Torque: 80 IN-LB, Conductor Type: Run And Tap: Solid Copperweld, Commercial Stranded And Solid Copper, Cross Flats: 0.5 IN, Width: 0.38 IN, Package: Clamshell

Product Details

General

Application	For Direct Burial Applications In Earth Or Concrete, Copper
Connector Type	Split Bolt
Construction Material - Main	Copper
Installation Torque Recommended in-lb	80 LBS/in
Material	Copper
Plated	N
Plating Type	Unplated
Sub Brand	SERVIT
Trade Name	SERVIT
Type	KS, Compact
UPC	781810360064
UPC 12 Digit	7818103600644

Dimensions

Dimension - B Length fraction	9/20 in
Dimension - B Length inch	0.45 in
Dimension - Cross Flats inch	0.5 in
Dimension - Length Overall inch	0.85 in
Dimension - Thread Size	-
Dimension - Width fraction	53/93 in
Dimension - Width inch	0.57 in

Conductor Related

Conductor - Copper Str Run	12;10
Conductor - Copper Str Tap	16;14;12;10

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No

Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	10
Number of Pieces in Package	5
Packaging Type	Clamshell

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)