



BURNDY Catalog Number
UPC Number
Description
Status

KPA8CUPRK
 7818103599699
 Scrulug POS Qty1=5pcs
 Active

Web Use
 BURNDY Product Line

Dimensional	
Length (in)	1.04
Thickness (in)	4/57
Height (in)	0.81
Stud Size (in)	#10
Thickness	0.07
D - in	0.56
Pad Width (in)	0.38
N (in)	0.22
Strip Length	15/32
General	
Number of Holes	1
Number of Screws	1
Product Description	Copper Alloy Scrulug Terminal, Conductor Range (Main/Primary): 14 AWG Solid - 6 AWG Stranded, Installation Torque: 35 IN-LB
Conductor(s)	
Copper Solid Size (Range)	14 AWG-6 AWG
Copper Stranded (Range)	14 AWG-6 AWG
Physical	
Screw Type	Slot
Type of Hardware	1/4 Dia. Slot Robertson
Installation Torque	35
Type of Plating	Unplated
Plated (Yes or No)	N
Product Material	Copper
Approvals / Certifications	
UL Listed	N
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175