



## KS23RK

by Burndy  
Catalog ID: KS23RK

Prop 65 Notice

High copper alloy Split Bolt, SERVIT,Torque:275 in-lb,Copper Conductor Stranded - Run Range:6 AWG-2 AWG.

Features: UL467 Listed For Direct Burial Applications In Earth Or Concrete, Compact, High-Strength, High Copper Alloy SERVIT Split-Bolt Has Free-Running Threads And Easy To Grip Wrench Flats, Highly Resistant To Cracking And Corrosion, Installation Torque: 275 IN-LB, Length: 1.54 IN, Cross Flats: 0.82 IN, Width: 0.62 IN, Package: Clamshell, Conductor Type: Run And Tap: Solid Copperweld, Commercial Stranded And Solid Copper, Type D Copperweld, Stranded Copperweld, Type A Copperweld

## Product Details

### General

|                                       |   |
|---------------------------------------|---|
| Application                           | For Direct Burial Applications In Earth Or Concrete, Copper |
| Connector Type                        | Split Bolt  |
| Construction Material - Main          | Copper  |
| Installation Torque Recommended in-lb | 275 LBS/in  |
| Material                              | Copper  |
| Plated                                | N   |
| Plating Type                          | Unplated  |
| Sub Brand                             | SERVIT  |
| Trade Name                            | SERVIT  |
| Type                                  | KS, Compact   |
| UPC                                   | 781810360033  |
| UPC 12 Digit                          | 7818103600333   |

### Dimensions

|                                 |          |
|---------------------------------|----------|
| Dimension - B Length fraction   | 18/25 in |
| Dimension - B Length inch       | 0.72 in  |
| Dimension - Cross Flats inch    | 0.82 in  |
| Dimension - Length Overall inch | 1.54 in  |
| Dimension - Thread Size         | -        |
| Dimension - Width fraction      | 23/25 in |
| Dimension - Width inch          | 0.92 in  |

### Conductor Related

|                                  |  |
|----------------------------------|--|
| Conductor - Copper Str Run       | 6 AWG;5 AWG;4 AWG;3 AWG;2 AWG  |
| Conductor - Copper Str Run Range | 6 AWG-2 AWG  |
| Conductor - Copper Str Tap       | 14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG |
| Conductor - Copper Str Tap Range | 14 AWG-2 AWG   |

Certifications and Compliance

|                                    |     |
|------------------------------------|-----|
| Certification - CSA Approved       | Yes |
| Certification - ETL                | No  |
| Standards - RoHS Compliance Status | CM  |
| UL Listed                          | Yes |

Logistics

|                             |           |
|-----------------------------|-----------|
| Minimum Pack Quantity       | 10        |
| Number of Pieces in Package | 2         |
| Packaging Type              | Clamshell |

For further technical assistance, please contact us

**BURNDY Headquarters**  
47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**  
8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)