

Product availability : Stock - Normally stocked in distribution facility



Price* : 29.60 USD



Main

| | |
|---------------------------------------|------------------------------------|
| Range of product | 8501R |
| Product or component type | Miniature Relay |
| Contacts material | Silver tin oxide |
| Switch function | SPDT |
| [Uc] control circuit voltage | 24 V DC |
| Rated power in HP | Not rated |
| Mounting support | Socket |
| Ambient air temperature for operation | -40...158 °F |
| Shape of pin | Spade |
| Product certifications | CE CSA RoHS UL recognized |
| Operating time | 20 ms pick-up 20 ms drop-out |
| Local signalling | No indicator |
| Control type | Without |
| Product compatibility | 8501NR41 |
| Relay type | Standard |

Ordering and shipping details

| | |
|-----------------------|----------------------|
| Category | 21143 - 8501 R |
| Discount Schedule | CP2 |
| GTIN | 00785901137054 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 5.999999999999998E-2 |
| Returnability | Y |
| Country of origin | CN |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1410 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|