

Product availability : Stock - Normally stocked in distribution facility



Price* : 39.30 USD



Main

Range of product	8501R
Product or component type	Miniature Relay
Contacts material	Silver tin oxide
Switch function	3PDT
[Uc] control circuit voltage	24 V DC
Rated power in HP	Not rated
Mounting support	Socket
Ambient air temperature for operation	-40...158 °F
Shape of pin	Spade
Product certifications	CE CSA RoHS UL recognized
Operating time	25 ms pick-up 20 ms drop-out
Local signalling	No indicator
Control type	Without
Product compatibility	8501NR43
Relay type	Standard

Ordering and shipping details

Category	21143 - 8501 R
Discount Schedule	CP2
GTIN	00785901137153
Nbr. of units in pkg.	1
Package weight(Lbs)	0.13
Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1410 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------