## Product data sheet Characteristics

## QO210

# QO Miniature Circuit Breaker 10A 2P 120/240V 10kA Plug-in Mount

Product availability: Stock - Normally stocked in distribution facility







#### Main

Man		<u></u>
Product or component type	Miniature circuit-breaker	ž.
Range of product	QO	
Line Rated Current	10 A	
System Voltage	120/240 V AC 48 V DC	o vilide of
Mounting mode	Plug-in	ier
Poles description	2P	- Vallice
Circuit breaker type	Standard	in a
Circuit breaker application	Not rated	Li
Electrical connection	Pressure plate	

#### Complementary

Breaking capacity	10 kA at: 120/240 V AC 5 kA at: 48 V DC	
Number of spaces required	2	
AWG gauge	AWG 14AWG 8 (copper or aluminium)	
Height	3 in	
Depth	2.91 in	
Width	1.5 in	, c

#### Environment

		-
Product certifications	UL listed CSA	—atation is
Ambient air temperature for operation	104 °F (40 °C)	—— ja

#### Ordering and shipping details

Category	00004 - QO,QOT 10-30A 1P:10-60A 2P

Discount Schedule	DE2A
GTIN	00785901205609
Nbr. of units in pkg.	5
Package weight(Lbs)	0.5300000000000003
Returnability	Υ
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

#### Contractual warranty

Warranty period	18 months