Product data sheet Characteristics

QOB225

QO Miniature Circuit Breaker 25A 2P 120/240V 10kA Bolt-on Mount

Product availability: Stock - Normally stocked in distribution facility







Main

IVICITI		9
Product or component type	Miniature circuit-breaker	y E
Range of product	QO	
Line Rated Current	25 A	
System Voltage	120/240 V AC 48 V DC	y vilide
Mounting mode	Bolt-on	
Poles description	2P	Salir
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	.i.
Electrical connection	Pressure plate	eg

Complementary

Breaking capacity	10 kA at: 120/240 V AC 5 kA at: 48 V DC	
Number of spaces required	2	
AWG gauge	AWG 14AWG 8 (copper or aluminium)	
Height	3 in	
Depth	2.91 in	
Width	1.5 in	, c

Environment

Environment		
Product certifications	UL listed CSA	
Ambient air temperature for operation	104 °F (40 °C)	——in

Ordering and shipping details

Category	00015 - QOB CIRCUIT BREAKERS

Discount Schedule	DE2
GTIN	00785901368281
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5700000000000006
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months