



**Product Number:** 49865

**Order Abbreviation:** QHE 3X32T8/UNV ISL-SC

**General Description:** 3-lamp 32wT8 High Efficiency Instant Start electronic ballast, universal voltage, low ballast factor, 10-pk

#### Product Information

|                                   |                               |
|-----------------------------------|-------------------------------|
| Abbrev. With Packaging Info.      | QHE3X32T8UNVLSLSC 10/CS 1/SKU |
| Ballast Factor                    | 0.78                          |
| Ballast Height H (in)             | 1.1810                        |
| Ballast Length L (in)             | 9.4690                        |
| Ballast Width W (in)              | 1.6810                        |
| Circuit Type                      | PARALLEL                      |
| Family Brand Name                 | QUICKTRONIC High-Efficiency   |
| Input Current (Amps)              | 0.00                          |
| Nominal Voltage (V)               | 120-277V                      |
| Number of Lamps                   | 3                             |
| Open Circuit Voltage (V)          | <600V                         |
| Power Factor                      | >0.98                         |
| Primary Lamp Type                 | FO32/XP                       |
| Sound Rating                      | A                             |
| Starting Method                   | INSTANT START                 |
| Starting Temperature - Fahrenheit | -20                           |
| Starting Temperature - Celsius    | -29                           |
| Total Harmonic Distortion (THD)   | <10%                          |
| Wiring Method                     | Leads                         |
| Max Case Temperature              | 70°C                          |



#### Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Input Frequency: 50/60Hz.
- Minimum starting temperature: -20 F / -29 C