

Product Number: 49598

Order Abbreviation: QTP 2x59T8/UNV ISN-SC

General Description: QTP2x59T8UNVISNSC 2-lamp 59wT8 (8') Instant Start electronic ballast, universal voltage, normal ballast factor, banded 10-pk



Product Information

Abbrev. With Packaging Info.	QTP2x59T8UNVISNSC 10/CS 1/SKU
Ballast Factor	0.88
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	<600V
Power Factor	>0.98
Primary Lamp Type	FO96T8 XP (59W)
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	LEADS
Max Case Temperature	70°C



Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 50/60Hz.