Product data sheet Characteristics

QOT1520

QO Tandem Mini Circuit Breaker 15/20A 1P 120/240V 10kA Plug-in Mount

Product availability: Stock - Normally stocked in distribution facility







Main

No. of the last of		
-		
Main		
Product or component type	Miniature circuit-breaker	
Range of product	QO	
Line Rated Current	15 A	
	20 A	
System Voltage	120/240 V AC	
Mounting mode	Plug-in	
Poles description	1P	
Circuit breaker type	Tandem	
Circuit breaker application	HACR rated	
Electrical connection	Pressure plate	
Complementary		
Breaking capacity	10 kA at: 120/240 V AC	
Number of spaces required	1	
AWG gauge	AWG 14AWG 8 (copper) AWG 12AWG 8 (aluminium)	
Environment		
Product certifications	UL listed	
	CSA	
Ambient air temperature for operation	104 °F (40 °C)	
O - 1 - 2 1 - 1 - 1 2 1 - 1		
Ordering and shipping details	00004 00 007 40 004 40 40 004 00	
Category	00004 - QO,QOT 10-30A 1P;10-60A 2P	
Discount Schedule	DE2A	
GTIN	00785901418047	
Nbr. of units in pkg.	10	
0 00 0047		

Complementary

Breaking capacity	10 kA at: 120/240 V AC
Number of spaces required	1
AWG gauge	AWG 14AWG 8 (copper) AWG 12AWG 8 (aluminium)

Environment

LITTIONICH		
Product certifications	UL listed CSA	
Ambient air temperature for operation	104 °F (40 °C)	

Ordering and shipping details

		٣
Category	00004 - QO,QOT 10-30A 1P;10-60A 2P	unoo
Discount Schedule	DE2A	iF.
GTIN	00785901418047	
Nbr. of units in pkg.	10	oct and the state of the state

Package weight(Lbs)	0.31		
Returnability	Υ		
Country of origin	MX		
Offer Sustainability			
Sustainable offer status	Green Premium product		
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity		
	Schneider Electric declaration of conformity		
REACh	Reference not containing SVHC above the threshold		
	Reference not containing SVHC above the threshold		

Contractual warranty

Product environmental profile

Product end of life instructions

Warranty period	18 months	

Need no specific recycling operations

Available