

# 82254

## SWITCH NOT FUSIBLE DT 240V 200A 2P NEMA1

Product availability : Stock - Normally stocked in distribution facility

Price\* : 1815.00 USD



### Main

Product or component type	Socket
Device short name	PK socket
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

### Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
Line Rated Current	16 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Secondary keyway clockwise position	Without
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Pins: stainless steel Springs: stainless steel Sleeves: nickel plated brass
Connections - terminals	Captive screws, completely loosened
Cable cross section	0...0.02 in <sup>2</sup> (2.5...10 mm <sup>2</sup> )
Cable outer diameter	0.45...0.83 in (11.5...21 mm)
Cable entry	Cable gland
Thread type	Pg 16
Base dimension	70 x 82 mm
Height	5.2 in (132 mm)
Width	2.76 in (70 mm)

Depth	3.62 in (92 mm)
Colour	Grey ( RAL 7035 )
Voltage colour	Blue

## Environment

Standards	EN 60309-1 EN 60309-2 EN 62262 IEC 60529 IEC 60695-2-11
IP degree of protection	IP67 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
Fire resistance	1562 °F (850 °C) conforming to IEC 60695-2-11
Relative humidity	50 % ( 104 °F (40 °C) ) 70 % ( 86 °F (30 °C) ) 90 % ( 68 °F (20 °C) )
Ambient air temperature for operation	95 °F (35 °C) ( 86400 s )

## Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	00785901453475
Nbr. of units in pkg.	1
Package weight(Lbs)	47.560000000000002
Returnability	Y
Country of origin	US

## Contractual warranty

Warranty period	18 months
-----------------	-----------