



CERTIFICATE OF COMPLIANCE

CERTIFICATE NUMBER: 101000-E2875D

ISSUE DATE: October 10, 2000 Page 1 of 3

Issued to: Square D Company
1601 Mercer Road
Lexington, KY. 40511 USA

Report Reference: E2875, February 9, 1972


This is to Certify that
representative samples of: Enclosed switches, types D121, D221, D321, DU221, DU321, DU222 &
DU322, suitable for use as service equipment. catalog numbers may have
suffix letters.

Have been investigated by Underwriters Laboratories Inc.® in accordance with the Standard(s)
indicated on this Certificate.


Standard(s) for Safety: UL 98, Enclosed Switches

Additional Information: See Addendum

Only those products bearing the UL Listing Mark should be considered as being covered by
UL's Listing and Follow-Up Service.

The UL Listing Mark generally includes the following elements: the symbol UL in a circle:  with the word "LISTED"; a control
number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate
UL Directory.

LOOK FOR THE UL LISTING MARK ON THE PRODUCT

Engineer: 
Tom Skibbs
Underwriters Laboratories Inc.

Review Engineer: 
Jake Killinger
Underwriters Laboratories Inc.



CERTIFICATE OF COMPLIANCE - ADDENDUM

CERTIFICATE NUMBER: 101000-E2875D
ISSUE DATE: October 10, 2000

Page 2 of 3

This is to verify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.


RATINGS


Current - 30 A and 60 A
Voltage - 240 V ac maximum

Short Circuit

When used with Class R fuses with Kit No. DRK-30 properly installed, fusible switches are suitable for use on circuits capable of delivering not more than 100,000 rms symmetrical amperes.

Unfused switches are suitable for use on circuits delivering not more than 100,000 rms symmetrical amperes for 30 A switches, and 50,000 for 60 A switches, when protected by fuses (circuit breaker) rated not more than the switch.

Engineer: 
Tom Skibbs
Underwriters Laboratories Inc.

Review Engineer: 
Jake Killinger
Underwriters Laboratories Inc.




CERTIFICATE OF COMPLIANCE - ADDENDUM


CERTIFICATE NUMBER: 101000-E2875D
ISSUE DATE: October 10, 2000

Page 3 of 3

This is to verify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

| | Amps | Volts(max) | Horsepower (+ indicates maximum rating) | | |
|--------|------|-------------|---|-------------|---------|
| | | | Current Voltage | Alternating | Direct |
| | | | 120 | 240 | 125 |
| | | | Phase | 1 | 3 |
| | | | Wires | 2 | 2 |
| D121-N | 30 | 120ac/125dc | | 1.5, 2+ | 2, 3+ |
| D221 | 30 | 240ac | | 1.5, 3+ | |
| D221-N | 30 | 240ac | | 1.5, 3+ | 3, 7.5+ |
| D321 | 30 | 240ac | | 1.5, 3+ | 3, 7.5+ |
| D321-N | 30 | 240ac | | | 3, 7.5+ |
| DU221 | 30 | 240ac | | 3 | |
| DU321 | 30 | 240ac | | 3 | 7.5 |
| DU322 | 30 | 240ac | | 10 | 15 |
| DU222 | 30 | 240ac | | 10 | |

Engineer: 
 Tom Skibbs
 Underwriters Laboratories Inc.

Review Engineer: 
 Jake Killinger
 Underwriters Laboratories Inc.