D224N

Safety switch, general duty, fusible, 200A, 2 poles, 60 hp, 120 VAC, NEMA 1, neutral factory installed





Main

Product	Single Throw Safety Switch
Current Rating	200 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R
Mounting Type	Surface
Number of Poles	2
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	240 V AC
Wire Size	AWG 6250 kcmil aluminium/copper

Complementary

Maximum Horse Power Rating	15 Hp 240 V AC 60 Hz 1 phase NEC 240.6 25 Hp 240 V AC 60 Hz 3 phase NEC 240.6 60 hp 240 V AC 60 Hz 3 phase NEC 430.52	
Tightening torque	275 lbf.in (31.07 N.m) AWG 6250 kcmil)	
Height	29 in (736.60 mm)	
Width	19 in (482.60 mm)	
Maximum Depth	8.25 in (209.55 mm)	

Ordering and shipping details

Ordering and shipping details	
Category	00006 - D & DU SW, NEMA1, 30-200A
Discount Schedule	DE1A
GTIN	00785901460749
Nbr. of units in pkg.	1
Package weight(Lbs)	41.8 lb(US) (18.96 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	8.10 in (20.574 cm)	
Package 1 width	30.50 in (77.47 cm)	
Package 1 Length	19.30 in (49.022 cm)	

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₽	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

18 months