

D324N

Safety switch, general duty, fusible, 200A,
3 poles, 60 hp, 240 VAC, NEMA 1, neutral
factory installed



Main

Product	Single Throw Safety Switch
Current Rating	200 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	240 V AC
Wire Size	AWG 6...250 kcmil aluminium/copper

Complementary

Maximum Horse Power Rating	15 Hp 240 V AC 60 Hz 1 phase NEC 240.6 25 Hp 240 V AC 60 Hz 3 phase NEC 240.6 60 hp 240 V AC 60 Hz 3 phase NEC 430.52
Tightening torque	275 lbf.in (31.07 N.m) AWG 6...250 kcmil)
Height	29 in (736.60 mm)
Width	19 in (482.60 mm)
Maximum Depth	8.25 in (209.55 mm)

Ordering and shipping details

Category	00006 - D & DU SW, NEMA1, 30-200A
Discount Schedule	DE1A
GTIN	00785901461470
Nbr. of units in pkg.	1
Package weight(Lbs)	44.01 lb(US) (19.96 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	8.60 in (21.844 cm)
Package 1 width	19.30 in (49.022 cm)
Package 1 Length	30.50 in (77.47 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	15
Package 2 Weight	932.00 lb(US) (422.748 kg)
Package 2 Height	45.30 in (115.062 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------