

QO310

QO Miniature Circuit Breaker 10A 3P 120/240V 10kA Plug-in Mount

Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|-----------------------------|---------------------------|
| Product or component type | Miniature circuit-breaker |
| Range of product | QO |
| Line Rated Current | 10 A |
| System Voltage | 120/240 V AC 48 V DC |
| Mounting mode | Plug-in |
| Poles description | 3P |
| Circuit breaker type | Standard |
| Circuit breaker application | HACR rated |
| Electrical connection | Pressure plate |

Complementary

| | |
|---------------------------|--|
| Breaking capacity | 10 kA at: 120/240 V AC 5 kA at: 48 V DC |
| Number of spaces required | 3 |
| AWG gauge | AWG 14...AWG 8 (copper or aluminium) |
| Height | 3 in |
| Depth | 2.91 in |
| Width | 2.25 in |

Environment

| | |
|---------------------------------------|------------------|
| Product certifications | CSA UL listed |
| Ambient air temperature for operation | 104 °F (40 °C) |

Ordering and shipping details

| | |
|----------|-----------------------------------|
| Category | 00012 - QO 3 POLE CIRCUIT BREAKER |
|----------|-----------------------------------|

| | |
|-----------------------|--------------------|
| Discount Schedule | DE2A |
| GTIN | 00785901477488 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.7700000000000002 |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|