



TERMINAL LUG DATA ‡

AMPERES	MAX WIRE	MIN WIRE	TYPE
100	#1/0 AWG	#12 AWG	AL
100	#1/0 AWG	#14 AWG	CU

DUAL DIMENSIONS: INCHES  
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	AMPERAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS																							
				240VAC						480VAC						600VAC						250 VDC		600 VDC			
				STD			MAX			STD			MAX			STD			MAX			STD	MAX	STD	MAX		
				1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø						
H223DS	240VAC, 250VDC	100	A	7 1/2*	-	15♣	15*	-	30♣	-	-	-	-	-	-	-	-	-	-	-	20*	-	-	-			
H223NDS	240VAC, 250VDC		B	7 1/2*	-	15♣	15*	-	30♣	-	-	-	-	-	-	-	-	-	-	-	20*	-	-	-			
H323DS	240VAC, 250VDC		B	7 1/2*	-	15♣	15*	-	30♣	-	-	-	-	-	-	-	-	-	-	-	20*	-	-	-			
H323NDS	240VAC, 250VDC	100	B	-	-	-	-	-	10*	-	25♣	30*	-	60♣	-	-	30	-	-	75	-	-	40*	50*			
HU363DS	600VAC, 600VDC	100	B	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
HU363DS	600VAC, 600VDC	100	C	-	-	-	20*	-	40♣	-	-	-	40*	-	75♣	-	-	-	-	-	40*	-	75	-	20*	-	50*

NOTES:  
 FINISH - TYPE 304 STAINLESS STEEL  
 UL LISTED - E2875  
 ALL NEUTRALS - INSULATED  
 SHORT CIRCUIT CURRENT RATINGS:  
 10,000 RMS SYMMETRICAL AMPERES  
 WHEN USED IN CONJUNCTION  
 WITH CLASS H OR K FUSES  
 200,000 RMS SYMMETRICAL AMPERES  
 WHEN USED IN CONJUNCTION WITH CLASS R, J OR T FUSES  
 \* USE OUTER SWITCHING POLES  
 ♣ IF CORNER GROUNDED DELTA SYSTEMS, INSTALL NEUTRAL AND USE OUTER SWITCHING POLES FOR UNGROUNDED CONDENSATORS.  
 ▲ NOT FOR CORNER GROUNDED DELTA SYSTEMS.  
 ‡ LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS ONLY.

HEAVY DUTY SAFETY SWITCHES  
 VISIBLE BLADES  
 100 AMPERE-SERIES F6  
 ENCLOSURE-NEMA TYPE 4, 4X AND 5 STAINLESS STEEL



DMC# 3182  
 NO.