


SEISMIC NOTES:
 USE (4) 1/4" DIA GRADE 5 STEEL MOUNTING BOLTS @ HOLES AA
 MAX CONFIGURED WEIGHT 10 LB FOR THE PURPOSE OF DETERMINING
 SEISMIC ANCHORAGE REQUIREMENTS. FOR ALL OTHER APPLICATIONS,
 CONTACT SQUARE D COMPANY.

DUAL DIMENSIONS: INCHES
 MILLIMETERS

WIRING DIAGRAMS

FUSIBLE



TERMINAL LUGS

AMPERES	MAX. WIRE	MIN. WIRE	TYPE
60	# 3 AWG	# 14 AWG	CU OR AL

KNOCKOUTS

SYMBOL	CONDUIT SIZE		DIAMETER	
	IN	MM	IN	MM
A	.50	13	.88	22
B	.75	19	1.13	29
C	1.00	25	1.38	35
D	1.25	32	1.75	44

CATALOG NUMBER	VOLTAGE RATINGS	AMPERAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS					
				240VAC				250 VDC	
				STD.		MAX.		STD.	MAX.
H222N	240VAC;250VDC	60	A	3▲	7 1/2●	10▲	15●	10▲	-
H322N	240VAC;250VDC	60	B	3▲	7 1/2●	10▲	15●	10▲	-

NOTES:
 UL LISTED - E2875
 FINISH GRAY BAKED ENAMEL
 ALL NEUTRALS - INSULATED GROUNDABLE
 WHEN MOUNTING THESE SWITCHES, ALLOW 3.00/[76] MIN CLEARANCE
 BETWEEN ENCLOSURES FOR OPENING OF SIDE HINGED DOOR.
 ▲ USE BOTH OUTER SWITCHING POLES
 ● IF CORNER GROUNDED DELTA, INSTALL NEUTRAL AND USE OUTER SWITCHING POLES FOR UNDERGROUNDED CONDUCTORS.

HEAVY DUTY SAFETY SWITCHES - SEISMIC
 VISIBLE BLADE TYPE
 60 AMPERE
 ENCLOSURE - NEMA TYPE 1



DWG# 3002S
 NO.