



NEMA TYPE 3R

WIRING DIAGRAMS

NOT FUSIBLE



TERMINAL LUGS ‡

AMPERES	MAX. WIRE	MIN. WIRE	TYPE
60	# 2 AWG # 2 AWG	#10 AWG #14 AWG	AL CU

KNOCKOUTS

SYMBOL	A	B	C	D
CONDUIT SIZE	.50	.75	1	1.25

DUAL DIMENSIONS: INCHES  
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	WIRING DIAG.	HORSEPOWER RATINGS	
			240VAC	
			MAX.	
DU222RB	240VAC	A	10	—
DU322RB	240VAC	B	10	15

NOTES:  
 FINISH — GRAY BAKED ENAMEL  
 UL LISTED — FILE E-2875  
 SUITABLE FOR USE AS SERVICE EQUIPMENT  
 TOP OF NEMA TYPE 3R SWITCHES HAVE PROVISIONS FOR MAXIMUM 2 1/2" BOLT-ON HUB.  
 SHORT CIRCUIT CURRENT RATINGS:  
 10,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS H OR K FUSES  
 100,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS R FUSES.  
 ‡ LUGS SUITABLE FOR 60°C OR 75°C COPPER OR ALUMINUM CONDUCTORS.

GENERAL DUTY SAFETY SWITCHES  
 VISIBLE BLADE TYPE  
 60 AMPERE  
 ENCLOSURE — NEMA TYPE 3R RAINPROOF



DWG# 1861  
 No.