



TERMINAL LUGS			
AMPERES	MAX WIRE	MIN WIRE	TYPE
30	#6 AWG	#12 AWG	AL
30	#8 AWG	#14 AWG	CU
60	#3 AWG	#12 AWG	AL
60	#3 AWG	#14 AWG	CU

KNOCKOUTS				
SYMBOL	C	D	E	F
CONDUIT SIZE	1	1.25	1.50	2

DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBERS				VOLTAGE RATINGS	AMPERE RATING	WIRING DIAG.	HORSEPOWER RATINGS														
NEMA TYPE 12K	NEMA TYPE 12	NEMA TYPE 12K	NEMA TYPE 12				240VAC				480VAC				600VAC		250 VDC		600 VDC		
WITH KNOCKOUTS	WITHOUT KNOCKOUTS	VIEWING WINDOW WITH KNOCKOUTS	VIEWING WINDOW WITHOUT KNOCKOUTS				STD.		MAX.		STD.		MAX.		STD.	MAX.	STD.	MAX.	STD.	MAX.	
							1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	3Ø	1Ø	3Ø				
H3612A	H3612AWK	---	---	600VAC;600VDC	30	B	-	-	-	-	5	15	-	15	7 1/2	-	20	-	-	10Δ	16Δ
H362A	H362AWK	H362AW	H362AWK/V	600VAC;600VDC	60	B	-	-	-	-	5▲	15◆	20Δ	30◆	15	-	50	-	-	25Δ	30Δ
HJ362A	HJ362AWK	HJ362AVW	HJ362AWK/VW	600VAC;600VDC	60	C	-	-	10Δ	20*	-	-	25Δ	50*	-	30Δ	60	-	10Δ	-	30Δ

NOTES:
 FINISH - GRAY BAKED ENAMEL
 UL LISTED - FILE E-2875
 ALL NEUTRALS - INSULATED GROUNDABLE
 SUITABLE FOR USE AS SERVICE EQUIPMENT
 SHORT CIRCUIT CURRENT RATINGS:

10,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS H OR K FUSES.
 200,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS R OR J FUSES.
 WHEN MOUNTING THESE SWITCHES, ALLOW 4.00 IN / 102 MM MIN. CLEARANCE BETWEEN ENCLOSURES FOR OPENING OF SIDE HINGED DOOR.

- * NOT APPLICABLE FOR CORNER GROUNDED DELTA.
- ▲ USE BOTH OUTER SWITCHING POLES.
- ◆ IF CORNER GROUNDED DELTA, INSTALL NEUTRAL AND USE OUTER SWITCHING POLES FOR UNGROUNDED CONDUCTORS.

HEAVY DUTY SAFETY SWITCHES
 VISIBLE BLADE TYPE
 30,60 AMPERE-SERIES FB
 ENCLOSURE - NEMA TYPE 12



DMC# 1896
 NO.