Product data sheet Characteristics

2510KO2

Manual Switch - Open - 3P - Toggle Operated - No Indicator - 600VAC

Product availability: Stock - Normally stocked in distribution facility



Price*: 139.11 USD



Main

Product or component type	Single Unit Manual Switch
Range of product	K

Complementary

Line Rated Current	30 A	
Motor power hp	2 hp at 115 V AC	
	1 hp at 90 V DC	
	2 hp at 115 V DC	
	1.5 hp at 230 V DC	
	7.5 hp at 230 V AC	-
	10 hp at 460 V AC	
	10 hp at 575 V AC	
System Voltage	600 V AC	
	230 V DC	1
Poles description	3P	
Control type	Toggle	
Phase	3 phases	
Local signalling	No indicator	
Motor starter type	Non reversing	
Electrical connection	Screw clamp terminals	-
AWG gauge	AWG 14AWG 10 (copper)	
Height	4.13 in	
Width	1.69 in	
Depth	2.34 in	

Environment

Product certifications	CE	- :
	UL recognized E42243 CCN NLRV2	- 0

CSA LR25490 class 3211 05

	CSA LR25490 class 3211 05	
NEMA degree of protection	Not rated (open device)	
Ordering and shipping detail	ls.	
Category	21102 - 2510,2511,2512 K	
Discount Schedule	CP1	
GTIN	00785901554585	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.3500000000000003	
Returnability	Y	
Country of origin	MX	
Offer Sustainability		
Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will be compliant on 3Q2014	
	Will be compliant on 3Q2014	
REACh	Reference not containing SVHC above the threshold	

Contractual warranty

Warranty period	18 months

Reference not containing SVHC above the threshold