Northbrook, Illinois • (847) 272-8800 Melville. New York • (631) 271-6200 Santa Clara, California • (408) 985-2400 Research Triangle Park, North Carolina • (919) 549-1400 Camas, Washington • (360) 817-5500

Page 1 of 2

## (UL) Underwriters Laboratories Inc.®

## **CERTIFICATE OF COMPLIANCE**

# CERTIFICATE NUMBER:131000-E33139DISSUE DATE:October 13, 2000

Issued to:	Square D Company 1601 Mercer Road Lexington, KY. 40517 USA
Report Reference:	E33139, January 24, 2000
This is to Certify that representative samples of:	Panelboards, typr NF, column type.

Have been investigated by Underwriters Laboratories Inc.<sup>®</sup> in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 67, Panelboards

Additional Information: See Addendum

Tom Skibbs

Underwriters Laboratories Inc.

## Only those products bearing the UL Listing Mark should be considered as being covered by UL's Listing and Follow-Up Service.

The UL Listing Mark generally includes the following elements: the symbol UL in a circle: W with the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

#### LOOK FOR THE UL LISTING MARK ON THE PRODUCT

Engineer:

**Review Engineer:** 

be Killinger /B

Øake Killinger V Underwriters Laboratories Inc.

A not-for-profit organization dedicated to public safety and committed to quality service

Northbrook, Illinois • (847) 272–8800 Melville. New York • (631) 271–6200 Santa Clara, California • (408) 985–2400

Research Triangle Park, North Carolina • (919) 549–1400 Camas, Washington • (360) 817–5500



### CERTIFICATE OF COMPLIANCE - ADDENDUM

#### CERTIFICATE NUMBER: 131000-E33139D ISSUE DATE: October 13, 2000

Page 2 of Z

This is to verify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

#### **RATINGS**

Current - 100A through 225 A maximum

Voltage -480 Y/227 V ac, 3ph-4w or 1ph-3w 240 V ac, 3ph-3w or 1ph-2w 240/120 V ac delta, 3ph-4w

120/240 V, 1ph-3w 208/120 V ac, 3ph-4w or 1ph-3w

Short Circuit

Except for when series connected ratings are employed, these panelboards have SCCR's equal to the lowest interrupting rating of any installed circuit breaker, but not greater than:

100,000 rms sym. amperes at 240 V ac 65,000 rms sym, amperes at 480 Y/277 V ac

Maximum SCCR's when series connected ratings are employed are: 200,000 rms sym. amperes at 240 V ac 200,000 rms sym. amperes at 480 Y/277 V ac

Engineer:

Tom Skibbs Underwriters Laboratories Inc. Review Engineer:

Jake Killinger / VB

Underwriters Laboratories Inc.

A not-for-profit organization dedicated to public safety and committed to quality service