

Product data sheet

Characteristics

2510MBA2

Manual Starter - NEMA 12 - 3P - Size M0 - No Indicator - 600VAC

Product availability : Stock - Normally stocked in distribution facility



Price* : 426.50 USD



Main

| | |
|---------------------------|----------------|
| Product or component type | Manual Starter |
| Range of product | M |
| NEMA size | M-0 |

Complementary

| | |
|----------------------------------|--|
| Control type | Push-button |
| Local signalling | No indicator |
| Motor power hp | 3 hp at 200...230 V AC 3 phases 5 hp at 380...575 V AC 3 phases |
| System Voltage | 600 V AC |
| Poles description | 3P |
| Motor starter type | Non reversing |
| Electrical connection | Pressure wire clamp |
| Thermal overload type | Melting alloy |
| Number of thermal units required | 3 |
| AWG gauge | AWG 14...AWG 8 (copper) |
| Auxiliary contact composition | Without |
| Height | 10.92 in |
| Width | 5.78 in |
| Depth | 5.76 in |

Environment

| | |
|---------------------------|---|
| Product certifications | UL listed file E42243 CCN NLRV CSA LR60905 class 3211 05 |
| NEMA degree of protection | NEMA 12 painted sheet steel |

Ordering and shipping details

| | |
|-----------------------|----------------------------|
| Category | 21103 - 2510,2511,2512 M,T |
| Discount Schedule | CP1 |
| GTIN | 00785901829720 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 7.129999999999999 |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|--------------------------|--|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Will not be compliant Will not be compliant |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|