



Catalog Home

Product Datasheet



ANDERSON FARGO

JLS1212 -- Compression Splice



Compression Splice, Uni-Grip, Jumper Loop-Min. Tension, Cond. Dia Range 1.046-1.140

Product Specifications

<p>Splice Type</p>	 <p>Transmission Compression Splices</p>
<p>Transmission Compression Series</p>	 <p>JLS & 40 Series Compression Splice Jumper Loop-Partial Tension AAC, AAAC, ACAR, & ACSR Conductor</p>
<p>PDF Catalog Page</p>	<p>Click HERE to view the web page.</p>
<p>Conductor Type</p>	<p>AAC, AAAC, ACAR, ACSR</p>
<p>Material</p>	<p>Aluminum Alloy</p>
<p>Minimum Conductor Diameter</p>	<p>1.046 in</p>
<p>Maximum Conductor Diameter</p>	<p>1.140 in</p>
<p>Length before Compression</p>	<p>12.00 in (304 mm)</p>
<p>Compression Method</p>	<p>Uni-Grip (single die system)</p>
<p>Die Size</p>	<p>12CD</p>
<p>Minimum Press (Tons)</p>	<p>60</p>
<p>Voltage Application</p>	<p>Std</p>
<p>UL Listed</p>	<p>No</p>
<p>Inhibitor Loaded</p>	<p>Yes</p>
<p>Material Type</p>	<p>Non-Standard</p>
<p>UPC Code</p>	<p>09635940114</p>
<p>Standard Package</p>	<p>1</p>
<p>Standard Package Unit</p>	<p>Each</p>

Min Order Qty	1
Weight / Ea.	1.882 lbs
Compressed Product Number	
JLS1212	

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.