


KNOCKOUTS							
SYMBOL	A	B	C	D	E	F	G
IN	.50	.75	1.00	1.25	1.50	2.00	2.50
MM	13	19	25	32	38	51	64



DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBER	MAXIMUM SYSTEM VOLTAGE	MAINS AMPERE RATING	SPACES	MAXIMUM NUMBER OF SINGLE POLE CIRCUITS	MAIN WIRE SIZE AWG AL/CU
QO12436L200TFT	120/240VAC 1Ø 3W	200	24	36	#4-250
QO12436M200TFT		200	24	36	
QO140L200G		200	40	40	
QO132M150		150	32	32	
QO140M200		200	40	40	
QO140M200C		200	40	40	
QO14060L200G		200	40	60	
QO14060M200		200	40	60	

NOTES:

UL LISTED - FILE E-6294
 NEUTRALS - INSULATED GROUNDABLE.
 LOAD CENTERS WITH "TFT" IN CATALOG NUMBER SUFFIX INCLUDE
 AN INSTALLED EQUIPMENT GROUND BAR AND FEED THRU LUGS.

QO LOAD CENTERS
 GENERAL PURPOSE NEMA TYPE 1 ENCLOSURE
 INDOOR

SQUARE D
 by Schneider Electric

DWG# 3008
 NO.