



Main

Product	Single Throw Safety Switch
Current Rating	30 A
Number of Poles	6
Voltage Rating	600 V AC
Disconnect Type	Non-fusible disconnect
Short Circuit Current Rating	200 kA maximum
Mounting Type	Surface
Factory Installed Neutral	None
Electrical Connection	Lugs
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R/12 galvanized steel
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper

Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	10 Hp 240 V AC 50...60 Hz 3 phase NEC 430.52 20 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 30 hp 600 V AC 50...60 Hz 3 phase NEC 430.52
Tightening torque	45 Lbf.in (5.08 N.m) 0.02 in ² (13.3 mm ²) AWG 6) 40 Lbf.in (4.52 N.m) 0.01 in ² (8.367 mm ²) AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) AWG 14...AWG 10)
Width	16.13 in (409.70 mm)
Height	20.5 in (520.70 mm)
Maximum Depth	6.8 in (172.72 mm)

Ordering and shipping details

Category	00116 - H&HU SW,4&6P,N12,30-200A
Discount Schedule	DE1
GTIN	00785901868354
Nbr. of units in pkg.	1
Package weight(Lbs)	29.85 lb(US) (13.54 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.40 in (18.796 cm)
Package 1 width	16.70 in (42.418 cm)
Package 1 Length	25.70 in (65.278 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------