

Product availability : Stock - Normally stocked in distribution facility



Price* : 182.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary voltage	240 x 480 V
Secondary voltage	120/240 V
Number of tap-offs	0

Complementary

Box number	1A
Phase	1 phase
Primary voltage	240 x 480 V : 120/240 V
Rated power in VA	0.05 kVA
Temperature rise	55 °C
Height	5 in
Width	4.47 in
Depth	3.44 in
Enclosure mounting	Wall mounted
Enclosure material	Painted sheet steel

Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	221 °F (105 °C)
Product certifications	CSA cULus UL listed

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2

GTIN	00785901875994
Nbr. of units in pkg.	1
Package weight(Lbs)	5.5099999999999998
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------