

Product availability : Stock - Normally stocked in distribution facility



Price* : 372.00 USD



Main

Product or component type	Industrial Control Transformer
Rated power in VA	250 VA
Primary voltage	208/240/277/380/480 V
Secondary voltage	24 V
Range of product	T

Complementary

Phase	1 phase
Rated power in VA	250 VA per UL 250 VA per CSA 250 VA per NOM 160 VA per CE
Primary voltage	208/240/277/380/480 V : 24 V
Temperature rise	80 °C
Electrical connection	Screw clamp terminals
Height	3.84 in
Width	4.5 in
Depth	4.74 in
Material	Copper winding
Product compatibility	FSC23

Environment

Product certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239 CE
NEMA degree of protection	Not rated (open device)
Insulation temperature	266 °F (130 °C)

Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901905899
Nbr. of units in pkg.	1
Package weight(Lbs)	10.609999999999999
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	10 years
-----------------	----------