

Product availability : Stock - Normally stocked in distribution facility



Price* : 696.00 USD



Main

Range of product	Modicon Momentum automation platform
Product or component type	Discrete solid state I/O base DC
Group of channels	4 groups of 4 inputs 2 groups of 4 outputs
Discrete input number	16 IEC 1131-2 Type 1
Discrete input logic	Positive
Discrete input voltage	24 V DC
Discrete output number	8
Discrete output type	Solid state switch
Discrete output voltage	<= 30 V DC 24 V DC
Discrete output logic	Positive
Protective treatment	TC

Complementary

[Us] rated supply voltage	24 V DC
Input voltage limits	- 3...30 V
Voltage state 0 guaranteed	-3...5 V
Voltage state 1 guaranteed	11...30 V
Current state 0 guaranteed	<= 1.2 mA
Current state 1 guaranteed	>= 2.5 mA
Input resistance	4 kOhm
Discrete output current	16 A per module 2 A per point 8 A per group
Leakage current	< 1 mA 24 V output circuit
Peak output current	2.8 A

Fault type	Overload on output Short circuit on output
Response time	< 0.1 ms from state 0 to state 1 on output < 0.1 ms from state 1 to state 0 on output 2.2 ms from state 0 to state 1 on input 3.3 ms from state 1 to state 0 on input
Isolation between channels and bus	500 V AC
Power dissipation	6.5 W <= 10 W
Marking	CE
Terminals description PLC n°1	(L+)PW_POS (1)IN_DIS#1 (16)IN_DIS#16 TB (2)IN_DIS#2 (15)IN_DIS#15 (3)IN_DIS#3 (10)IN_DIS#10 (11)IN_DIS#11 (12)IN_DIS#12 (9)IN_DIS#9 (7)IN_DIS#7 (13)IN_DIS#13 (6)IN_DIS#6 (5)IN_DIS#5 (8)IN_DIS#8 (4)IN_DIS#4 (M-)PW_NEG (14)IN_DIS#14
Terminals description PLC n°2	TB_1 (4)OUT_DIS#4 (1L+)PW_POS (2L+)PW_POS (1)OUT_DIS#1 (3)OUT_DIS#3 (6)OUT_DIS#6 (2)OUT_DIS#2 (8)OUT_DIS#8 (7)OUT_DIS#7 (5)OUT_DIS#5
Current consumption	250 mA 24 V DC
Depth	1.87 in (47.5 mm)
Height	5.57 in (141.5 mm)
Width	4.92 in (125 mm)
Product weight	0.49 lb(US) (0.22 kg)

Environment

Product certifications	UL CSA
Resistance to electrostatic discharge	4 kV contact IEC 801-2 8 kV on air IEC 801-2
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) 80...1000 MHz IEC 801-3
Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % without condensation
Operating altitude	<= 16404.2 ft (5000 m)

Ordering and shipping details

Category	18206 - MOMENTUM PROCESSORS,I/O BASES,CONN.
Discount Schedule	PC31
GTIN	00785901307983
Nbr. of units in pkg.	1
Package weight(Lbs)	0.9200000000000004

Returnability	Y
Country of origin	ID

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1350 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------