# Product data sheet Characteristics

# 9001SKP38LRR31 PILOT LIGHT 120V 30MM SK +OPTIONS

Product availability: Stock - Normally stocked in distribution facility



Price\*: 154.60 USD



#### Main

Product or component type	Pilot light
Lens type	Fresnel plastic
Light block supply	Direct 120 V

#### Complementary

Main		
Product or component type	Pilot light	
Lens type	Fresnel plastic	
Light block supply	Direct 120 V	
_		
Complementary		
Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Shape of signaling unit head	Round	
Cap/Operator or lens colour	Red	
Light source	Red LED	
Bulb base	BA 9s	
[Us] rated supply voltage	2428 V AC/DC	
Operating position	Any position	
Operating mode	Normal	
CAD overall width	2.13 in (54 mm)	
CAD overall height	2.76 in (70 mm)	
CAD overall depth	1.65 in (42 mm)	
Device presentation	Complete product	
Environment		
Environment  Protective treatment	TC	
Protective treatment		
IP degree of protection	IP66	
Ordering and shipping details		
Category	21429 - 9001 SK,SKY	
Discount Schedule	CS1	
Iul 27, 2047		

## Environment

Protective treatment	TC	
IP degree of protection	IP66	

### Ordering and shipping details

Category	21429 - 9001 SK,SKY	É
Discount Schedule	CS1	

GTIN	00785901041436	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.179999999999999	
Returnability	Υ	
Country of origin	MX	
Offer Sustainability		
Offer Sustainability RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity	
	Compliant - since 0921 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity	

18 months

Warranty period