



| SUPPLY | CONSUMPTION | AUX. CONTACTS | | CODE (1) |
|--------|-------------|---------------|----|----------|
| | | NO | NC | |
| AC | 4.5 VA | 4 | - | 40 |
| | | 3 | 1 | 31 |
| | | 2 | 2 | 22 |

| CA-KN RELAYS | | | |
|----------------------|-------------|-------------|-------------|
| VOLTS AC 50/50 HZ | CODE (2) | CODE (3) | CODE (4) |
| 12 | J7 | JD | JW3 |
| 24 | B7 | BD | BW3 |
| 36 | C7 | CD | |
| 42 | D7 | | |
| 48 | E7 | ED | EW3 |
| 60 | | ND | |
| 72 | | SD | SW3 |
| 100 | | KD | |
| 110 | F7 | FD | |
| 120 | B7 | | |
| 125 | | GD | |
| 127 | FC7 | | |
| 208 | L7 | | |
| 220 | | MD | |
| 220/230 | M7 | | |
| 230 | P7 | MPD | |
| 230/240 | U7 | | |
| 240 | | MUD | |
| 250 | | UD | |
| 380/400 | Q7 | | |
| 400 | V7 | | |
| 400/415 | N7 | | |
| 440 | R7 | | |
| 480 | T7 | | |
| 500 | S7 | | |
| 600/600 | Y7 | | |

CA2KN = AC CONTROL RELAY
 CA3KN = DC CONTROL RELAY
 CA4KN = DC LOW CONSUMPTION CONTROL RELAY

Catalog Number: CA2KN(1)(2), CA3KN(1)(3), CA4KN(1)(4)
 Ratings: -
 UL File/Class: -
 CSA File/Class: -
 Meets Standards: IEC 947, NF C 63-140, VDE 0660, BS 5424, CE
 Weight: -
 Wire Size: MINI (1) 16 AWG, MAX (2) 12 AWG
 Terminal Torque: 7 LB-IN
 Mounting Hwd.: 35mm DIN TRACK OR PANEL MOUNT

DUAL DIMENSIONS: INCHES
 MILLIMETERS

IEC INDUSTRIAL CONTROL RELAY (K-LINE)
 CA2KN(1)(2), CA3KN(1)(3), CA4KN(1)(4)



DWG# E0702001-01
 NO.