

Type RW Reducing Washers

NEC/CEC:
Listed for Ordinary Locations

Features

- To reduce a knockout or sliphole in a sheet metal enclosure to a smaller trade size.

Standard Materials

- Steel

Standard Finishes

- Zinc pre-galvanized


NEC/CEC Certifications and Compliances

- UL Standard: ANSI/UL 514B
- UL Listed: E-14817
- CSA Standard: C22.2 No. 18
- CSA Certified: 057250
- NEMA: FB-1

| Trade Size (Inches) | Dimensions in Millimeters (Inches) | | Catalog Number |
|---------------------|------------------------------------|---------------|----------------|
| | A | B | |
| 3/4 x 1/2 | 22.35 (0.88) | 36.58 (1.44) | RW-2S |
| 1 x 1/2 | 22.35 (0.88) | 44.45 (1.75) | RW-3S |
| 1 x 3/4 | 28.19 (1.11) | 44.45 (1.75) | RW-4S |
| 1-1/4 x 1/2 | 22.35 (0.88) | 55.63 (2.19) | RW-5S |
| 1-1/4 x 3/4 | 28.19 (1.11) | 55.63 (2.19) | RW-6S |
| 1-1/4 x 1 | 34.80 (1.37) | 55.63 (2.19) | RW-7S |
| 1-1/2 x 1/2 | 22.35 (0.88) | 63.50 (2.50) | RW-8S |
| 1-1/2 x 3/4 | 28.19 (1.11) | 63.50 (2.50) | RW-9S |
| 1-1/2 x 1 | 34.80 (1.37) | 63.50 (2.50) | RW-10S |
| 1-1/2 x 1-1/4 | 43.94 (1.73) | 63.50 (2.50) | RW-11S |
| 2 x 1/2 | 22.35 (0.88) | 76.20 (3.00) | RW-12S |
| 2 x 3/4 | 28.19 (1.11) | 76.20 (3.00) | RW-13S |
| 2 x 1 | 34.80 (1.37) | 76.20 (3.00) | RW-14S |
| 2 x 1-1/4 | 43.94 (1.73) | 76.20 (3.00) | RW-15S |
| 2 x 1-1/2 | 50.29 (1.98) | 76.20 (3.00) | RW-16S |
| 2-1/2 x 1/2 | 22.35 (0.88) | 88.90 (3.50) | RW-17S |
| 2-1/2 x 3/4 | 28.19 (1.11) | 88.90 (3.50) | RW-18S |
| 2-1/2 x 1 | 34.80 (1.37) | 88.90 (3.50) | RW-19S |
| 2-1/2 x 1-1/4 | 43.94 (1.73) | 88.90 (3.50) | RW-20S |
| 2-1/2 x 1-1/2 | 50.29 (1.98) | 88.90 (3.50) | RW-21S |
| 2-1/2 x 2 | 62.23 (2.45) | 88.90 (3.50) | RW-22S |
| 3 x 1 | 34.80 (1.37) | 104.90 (4.13) | RW-25S |
| 3 x 1-1/4 | 43.94 (1.73) | 104.90 (4.13) | RW-26S |
| 3 x 1-1/2 | 50.29 (1.98) | 104.90 (4.13) | RW-27S |
| 3 x 2 | 62.23 (2.45) | 104.90 (4.13) | RW-28S |
| 3 x 2-1/2 | 75.44 (2.97) | 104.90 (4.13) | RW-29S |
| 3-1/2 x 1-1/2 | 50.29 (1.98) | 117.60 (4.63) | RW-34S ① |
| 3-1/2 x 2 | 62.23 (2.45) | 117.60 (4.63) | RW-35S ① |
| 3-1/2 x 2-1/2 | 75.44 (2.97) | 117.60 (4.63) | RW-36S ① |
| 3-1/2 x 3 | 91.19 (3.59) | 117.60 (4.63) | RW-37S ① |
| 4 x 2 | 63.50 (2.50) | 130.81 (5.15) | RW-43S ① |
| 4 x 2-1/2 | 75.44 (2.97) | 130.81 (5.15) | RW-44S ① |
| 4 x 3 | 91.19 (3.59) | 130.81 (5.15) | RW-45S ① |
| 4 x 3-1/2 | 104.90 (4.13) | 130.81 (5.15) | RW-46S ① |



Type RW



① Not CSA Certified.

Knockout Blanks and Fixture Stems

NEC/CEC:
Listed for Ordinary Locations

Applications





- Knockout blank: to close a knockout or siphole in a sheet metal enclosure.
- Fixture stems: to suspend fixtures from threaded rods.

Material

- Blanks: steel
- Fixture stem: malleable iron

NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14817
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E14817
- NEMA: FB-1

| | Trade Size (Inches) | Dimensions in Millimeters (Inches) | | | Weight per 100 kg (lb) | Appleton™ Catalog Number | O-Z/Gedney™ Catalog Number | |
|---|------------------------|------------------------------------|----------------|----------------|---------------------------|--------------------------------|----------------------------------|---|
| | | A | B | C | | | | |
| Open Type No Bolt Fixture Stems – Malleable Iron | | | | | | | | |
|  | 3/8 Male | 49.3 (1.94) | 17.5 (0.69) | 38.1 (1.50) | 3.63 (8.00) | NBFS-38 | — |  |
| | 3/8 Male | 49.3 | 17.5 | 38.1 | 3.63 | NBFS-38M | — | |
| | 1/8 Female | 49.3 (1.94) | 17.5 (0.69) | 38.1 (1.50) | 3.63 (8.00) | | | |
| Snap-in Knockout Blanks – Steel ① | | | | | | | | |
|  | 1/2 | 26.9 (1.06) | 7.9 (0.31) | — | 0.45 (1.00) | S50 | KO-50S |  |
| | 3/4 | 31.8 (1.25) | 7.9 (0.31) | — | 0.91 (2.00) | S75 | KO-75S | |
| | 1 | 38.1 (1.50) | 8.6 (0.34) | — | 1.36 (3.00) | S100 | KO-100S | |
| | 1-1/4 | 46.0 (1.81) | 7.9 (0.31) | — | 1.45 (3.20) | S125 | KO-125S | |
| | 1-1/2 | 56.4 (2.22) | 9.7 (0.38) | — | 2.18 (4.80) | S150 | KO-150S | |
| | 2 | 68.3 (2.69) | 9.7 (0.38) | — | 2.72 (6.00) | S200 | KO-200S | |

① Not UL Listed.