



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

Search Parameters:

[e-Catalog](#) > [Transformers](#) > Dry Type, Encapsulated, Enclosed

Transformers, Dry Type, Encapsulated, Enclosed

Product #: 9T51B0009

Short Description: .750 KVA, 240X480 TO 120/240, 60 HZ

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

Category	Single-Phase:
Phase	1
PriVoltage	240x480
SecVoltage	120/240
KVA	0.75 KVA
Coil Material	CU
TempRise	100 °C
ElecShield	N
SubType	Standard
Frequency	60 Hz
UL	Yes
FrameSize	12200
cUL	Yes
CE	No
Width	7.88 in
Depth	5.5 in
Height	9.62 in
TempClass	180 °C
AmbTemp	40 °C
InsulSys	IS-12
EnergyEfficiency	None
KFactor	K1
Enclosure Type	NEMA 3R
Sound	Std
GSA Compliance	Yes
GO Schedule	90A
List Price	\$254



[View Larger](#)

Publications/Resources

[9T51B0009](#)

Additional Resources for Single-Phase: .050kVA-3kVA and 5kVA-25kVA

[Application and Technical Brochures](#)

[Drawings-Outline and Dimensional Buy Log :8-50](#)

[Control Log : 15-9](#)

These GE transformers feature an encapsulated core and coil in a NEMA 3R non-ventilated weatherproof enclosure.

- UL Listed
- C-UL Listed
- Knockouts provided on back and bottom
- High grade silicon steel core
- Mounting holes on side for easy access
- Wiring compartment includes ground stud

