Ty-Rap[®] Installation Tools

Lightweight. Economical. Durable. Perfect for spot-tying!

Ty-Rap® Cable Tie Installation Tool — Light Duty

- Installs Ty-Rap cable ties up to .301" wide by .080" thick
- · Designed for use by both left- and right-handed operators
- · Lightweight, high-impact polymer and steel components

They cinch up the tie with a squeeze action, and cut away the excess tail when twisted 180°. A specially designed pawl cuts away the tail if the tension limit is exceeded, thereby preventing the cable tie from being over-tightened.



STD. PKG. Cat. No.	DESCRIPTION	TIE BODY WIDTH IN./MM	STD. PKG. QTY.
WT1-TB	Cable Tie Installation Tool, 18–50 lbs. (80–222.4N)	.0918/2.39-4.67	1
WT2-TB	Cable Tie Installation Tool, 50–120 lbs. (222.4–533.8N)	.18301/4.67-7.65	1

Cuts tail off — flush.

Ty-Rap® Cable Ties Installation Tool — Metallic


- Installs Ty-Rap[®] cable ties
- · Rugged metallic construction
- Pistol-grip installation tool
- · Easy tension adjustment
- · Tensions and cuts tie tail off flush



STD. PKG.	DESCRIPTION	TIE BODY	STD.
CAT. NO.		WIDTH IN./MM	PKG. QTY.
WT193A	Cable Tie Installation Tool, 18–50 lbs. (80–222.4N)	.0918/2.39-4.67	1

Easy tension adjustment!

Ty-Rap® Heavy-Duty Installation Tool — Mil Spec Approved



- Rugged metallic construction
- Pistol-grip installation tool
- · Tensions and cut cable tie tail off flush

STD. PKG.	DESCRIPTION	TIE BODY WIDTH IN./MM	STD. PKG. QTY.
WT199	Installation Tool, 18–50 lbs. (80–222.4N)	.0918/2.39-4.67	1
WT197	Installation Tool, 50-120 lbs. (222.4-533.8N)	.1830/4.67-7.65	1
* Mil Spec	Approved (WT199 — MS90387-1, WT197 —	- MS90387-2)	

Makes tie installation easy!

Ty-Rap[®] Installation Tool — Deltec[®] & Stainless Steel

WT3I

 Installs both self-locking Ty-Rap® cable ties and lashing ties

WT3S

Installs stainless steel ties

WT3D

STD. PKG.		TIE BODY	STD.
CAT. NO.	DESCRIPTION	WIDTH IN./MM	PKG. QTY.
WT3D	Deltec Installation Tool	.1850/4.67-12.70	1
WT3S	Stainless Steel Installation Tool	Up to .50/12.70	1



United States

Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354 **Technical Services**

Tel: 888.862.3289

