



BURNDY Catalog Number
UPC Number
Description
Status

BISR250DB
7818102880611
250-4/0 DIRECTBURIALUNIT
Active

Web Use
BURNDY Product Line

Screw Size
Width (in)
Hex Size (Key)
Length (in)
Height (in)

Dimensional

5/8
1.18
5/16
6.70
2.17

Min Voltage Rating

600

Number of Ports
Number of Screws

Electrical

600

General

2

2

Product Description

In-Line Splice/Reducer, 2 Port, 4/0
AWG-250 kcmil, Al/Cu Rated

Aluminum Size (Range)
Copper Solid Size (Range)
Copper Stranded (Range)

Conductor(s)

4/0-250 kcmil
N/A
4/0 AWG-250 kcmil

Insulation Type
Type of Hardware
Installation Torque
Type of Plating
Plated (Yes or No)
Product Material

Physical

Plastisol
Aluminum
360
Unplated
N
Aluminum

UL Listed
Rated for Direct Burial
ROHS Compatible
Industry Standards

Approvals / Certifications

Y
Y
Compliant
UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175