

PRODUCT DATA SHEET



Product Description

A blue tacky, aluminum complex grease using a highly refined base oil. It has been formulated with a polymer to provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe

water conditions.

Applications

Anti-friction bearings, blocks, boat trailer bearings, deck equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel

bearings, winches

14 Ounce Can

Unit Package Description

Sta-Lube

Brand

Marine Grease for Boat Trailer

Generic Description 1
Net Fill

14 Wt Oz

UPC Code

072213312102

Unit Dimensions

3.44H x 4.13W x 4.13D in

Units Per Case

12

108

Case Dimensions

 $3.5H \times 12.5W \times 17D in$

Cases Per Pallet

13 lbs

Case Weight
I 2 of 5 Code

30072213312103

Appearance

Blue Semi-Solid to Solid Grease

Base Type

Aluminum Complex

Flash point (F)

Flash point (C) >232.2°C

Flammability Class - CPSC Nor

None

>450°F

Spec Gravity Concentrate

0.9

NLGI Grade

Plastic Safe

Not Determined

Evaporation Rate

Slow

Working Temp (F)

0 to 325°F

Last revised: 2/28/2018

Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com





PRODUCT DATA SHEET



Working Temp (C) -17.8 to 162°C

Drop Point 500°F

Leakage 5

Oxidation Stability 5

Pour Point (F) 0°F

Pour Point (C) -17.78°C

ISO Viscosity Grade 180 Cst at 40°C

Water Washout 5% at 175°F

Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 0

def)

VOC g/L (Consumer

Product def)

VOC lbs/gal (Consumer

Prod def)

VOC Category Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.

0

0

Last revised: 2/28/2018

Page 2 of 2

