

PRODUCT DATA SHEET

Constant Velocity (CV) Joint Grease, 4 Wt Oz No. SL3174 | Item# 1007886 | Case# 1007885

Product Description

Applications

A special lithium base grease fortified with molybdenum disulfide and polymers. It is used for the installation & repair work on CV joints. Will extend the life of the CV joint & the additives will sustain the shock loads encountered in the CV joints

CV boot, CV joints found in front wheel drive passenger vehicles, safe for both domestic & foreign CV joints

Unit Package Description 4 ounce Tube Brand Sta-Lube **Generic Description 1** Constant Velocity Joint Grease Net Fill 4 Wt Oz **UPC** Code 072213317404 Unit Dimensions 9.25H x 4W x 1.5D in Units Per Case 12 **Case Dimensions** 9.75H x 5.13W x 11D in Cases Per Pallet 175 Case Weight 5 lbs 30072213317405 I 2 of 5 Code Dark Gray Semi-Solid to Solid Grease Appearance Base Type Lithium-12 Flash point (F) >450°F Flash point (C) >232°C Flammability Class - CPSC None 0.9 at 60°F Spec Gravity Concentrate NLGI Grade 1 Timken OK Load Lbs. 50 Lbs Plastic Safe Yes **Evaporation Rate** <0.01 (Butyl Acetate=1) 10 to 275⁻F Working Temp (F) -12.2 to 134°C Working Temp (C)

EXTREME PRESSURE

ANTI-SEIZE

MOLY DISULFIDE

WARNING

4 oz. (113.4 g)

E AND SKIN IRRITATION extension on back party.


Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001.2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.

Last revised: 11/30/2017

Page 1 of 2



 $CRC^{\circledast},$ K&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with $^{\circledast}$ and $^{\intercal}$ are trademarks



PRODUCT DATA SHEET



4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point	350°F
Elastomer Compatibility	0 to 40% vol ; 0
Leakage	Not Determined
Oil Separation	<10%
Oxidation Stability	<5 Lbs
Pour Point (F)	10°F
Pour Point (C)	-12.22°C
ISO Viscosity Grade	110
Water Washout	Not Determined
Worked Penetration	300 to 330
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	<0.1
VOC g/L (Consumer Product def)	<0.9
VOC lbs/gal (Consumer Prod def)	<0.007
VOC Category	Not Regulated
Removal (How To)	Remove with a d

; 0 to 15 hard ned ned d

Remove with a degreaser or brake cleaner product.

and adheres to the strictest guidelines for quality in all facets of research, development and production.



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



CRC[®], K&W[®], Sta-Lube[®], Marykate[®] and products denoted with [®] and [™] are trademarks of CRC Industries, Inc.

Last revised: 11/30/2017 Page 2 of 2