



**POWER
SYSTEMS, INC.**

In the world of power transmission and distribution, look to Hubbell.

**Interactive
eCatalog**

Catalog Home

Product Datasheet

ANDERSON FARGO

SEDA3309SSACNT -- Compression Deadend



Compression Deadend, Conventional 2-Die, Single Tongue, for ACSS 795.0 kcmil 26/7, Without Terminal

Product Specifications

Category Image



Aluminum
Conventional (two die)
AAC, ACSR, & ACSS
Conductor

Series Image (Comp Assy)



PDF Catalog Page

[Click HERE to view the web page.](#)

Terminal Option

Without

Style

Conventional 2-Die, Single Tongue

Outside Diameter

1.108 in

Type

Compression

Material

Aluminum/Steel

Compression Method

Conventional (2 die system)

Aluminum Die

30AH

Steel Die

16SH

Minimum Press (Tons)

60

Voltage Application

EHV & Std

Inhibitor Loaded

No

Body Material

Seamless Extruded Aluminum Alloy

Eye Material

Galvanized Forged Steel

Hardware Material	Aluminum Alloy
Length before Compression	21.8 in (554 mm)
Dimension A	2.62 in (66.5 mm)
Dimension B	1.24 in (31.5 mm)
Dimension C	0.55 in (14.0 mm)
Pad Width	3.0 in (76 mm)
Bolt Holes	4
Conductor Range Minimum - Maximum	ACSS 795.0 kcmil (26/7) Drake
Weight / Ea.	11.32 lbs
Standard Package	6
UPC Code	09635936375

Notes

To specify double-tongue deadend, change first character of Catalog Number from S to D.

Compressed Product Number

SEDA3309SSACNT



Dimensions

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.