



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip unit technology	Thermal-magnetic
Breaking capacity code	G

Complementary

Complementary		
Line Rated Current	15 A	
Poles description	3P	
Breaking capacity	65 kA at 240 V AC 35 kA at 480 V AC 18 kA at 600 V AC 20 kA at 500 V DC 20 kA at 250 V DC	
System Voltage	250 V DC 500 V DC 600 V AC	
Continuous current rating	80 %	_
Mounting mode	I-Line	
Electrical connection	I-Line connection line Lugs load	
AWG gauge	AWG 14AWG 3/0 (aluminium/copper)	
Phase connection	ABC	
Magnetic hold current	350 A	
Magnetic tripping current	750 A	
Height	9.73 in	,
Width	4.48 in	
Depth	4.8 in	

Environment

product certifications	CE CSA IEC UL listed
ambient air temperature for operation	104 °F (40 °C)

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0832 - Schneider Electric declaration of conformity	Compliant - since 0832 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
DIND, which is known to the State of California to course	DIND, which is known to the State of California to cause cancer, and

DINP, which is known to the State of California to cause DINP, which is known to the State of California to cause cancer, and

cancer, and	
DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.	DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov
Contractual warranty	
Warranty period	18 months

