## Product data sheet Characteristics

# HLA36015

## PowerPact H I-Line Circuit Breaker,ThermMagn,15A,3P,600V,50kA

Product availability: Stock - Normally stocked in distribution facility





Price\*: 2993.00 USD



#### Main

Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip unit technology	Thermal-magnetic	
Breaking capacity code	Ļ	

#### Complementary

Line Rated Current	15 A	
Poles description	3P	
Breaking capacity	125 kA at 240 V AC 100 kA at 480 V AC 50 kA at 600 V AC 20 kA at 250 V DC 50 kA at 500 V DC	A bo is od for Adda
System Voltage	500 V DC 600 V AC	
[lcs] rated service short-circuit breaking capacity	80 %	0.150 1.151
Mounting mode	I-Line	
Electrical connection	I-Line connection line Lugs load	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
AWG gauge	AWG 14AWG 3/0 (aluminium/copper)	9
Phase connection	ABC	
Magnetic hold current	350 A	
Magnetic tripping current	750 A	

#### Environment

Product certifications	CSA
	UL listed

CE	
IEC	

Ambient air temperature for operation	104 °F (40 °C)

### Ordering and shipping details

Category	01122 - HL, JL I-LINE BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901700647
Nbr. of units in pkg.	1
Package weight(Lbs)	5.480000000000004
Returnability	Υ
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

#### Contractual warranty

Contractual Warranty		
Warranty period	18 months	