



TERMINAL LUG DATA ‡			
AMPERES	MAX WIRE	MIN WIRE	TYPE
60	#3 AWG	#12 AWG	AL
60	#3 AWG	#14 AWG	CU

DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	AMPERAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS												250 VDC		600 VDC								
				240VAC						480VAC						600VAC										
				STD			MAX			STD			MAX			STD			MAX			STD	MAX	STD	MAX	
H362SS	600VAC,600VDC	60	A	-	-	-	-	-	-	5*	-	-	15♦	20*	30♦	-	-	-	15	-	-	50	-	-	25	30
HU362SS	600VAC,600VDC	60	B	-	-	-	10*	-	15♦	-	-	-	25*	-	30♦	-	-	-	30*	-	60	-	10*	-	30*	

NOTES:
FINISH - TYPE 316 STAINLESS STEEL
UL LISTED - E2875
CSA - FILE PER REFERENCE 158337 REPORT 1100884 (LL 89067-16).
ALL NEUTRALS - INSULATED
SHORT CIRCUIT CURRENT RATINGS:
10,000 RMS SYMMETRICAL AMPERES
WHEN USED IN CONJUNCTION
WITH CLASS H OR K FUSES

200,000 RMS SYMMETRICAL AMPERES WHEN USED
IN CONJUNCTION WITH CLASS R, J OR T FUSES

* USE BOTH OUTER SWITCHING POLES

♦ IF CORNER GROUNDED DELTA SYSTEM, INSTALL NEUTRAL AND USE OUTER SWITCHING
POLES FOR UNGROUNDED CONDUCTORS.

‡ LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS ONLY.

HEAVY DUTY SAFETY SWITCHES
VISIBLE BLADES
60 AMPERE-SERIES F6
ENCLOSURE-NEMA TYPE 4, 4X AND 5 STAINLESS STEEL



DWG# 3333
NO.