## Product data sheet Characteristics

# **HGA36060**

# PowerPact H I-Line Circuit Breaker, Therm Magn, 60A, 3P, 600V, 18kA

Product availability: Stock - Normally stocked in distribution facility





Price\*: 1575.00 USD



### Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip unit technology	Thermal-magnetic
Breaking capacity code	G

#### Complementary

500 m		
No. 144		
1. 1. 1. 1. 1. 1.		
Main		,
Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip unit technology	Thermal-magnetic	
Breaking capacity code	G	
Complementary		
Line Rated Current	60 A	
Poles description	3P	
Breaking capacity	65 kA at 240 V AC	
2. caiming capacity	35 kA at 480 V AC	
	18 kA at 600 V AC	
	20 kA at 500 V DC 20 kA at 250 V DC	
Contains Valta as	500 V DC	
System Voltage	600 V AC	
[lcs] rated service short-circuit	80 %	
breaking capacity		
Mounting mode	I-Line	
Electrical connection	I-Line connection line	
	Lugs load	
AWG gauge	AWG 14AWG 3/0 (aluminium/copper)	
Phase connection	ABC	
Magnetic hold current	800 A	
Magnetic tripping current	1450 A	
Environment		
Product certifications	UL listed	
	CSA	
I.J. 27, 2047		

#### Environment

Draduat cortifications	III lintad	
Product certifications	UL listed	
	004	
	CSA	

FC.	
`:F	

Ambient air temperature for operation	104 °F (40 °C)

### Ordering and shipping details

Category	01117 - HG, HJ, JG, JJ I-LINE BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901795032
Nbr. of units in pkg.	1
Package weight(Lbs)	5.410000000000001
Returnability	Υ
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

#### Contractual warranty

Contractual Warranty		
Warranty period	18 months	