

# HDA36060

## PowerPact H I-Line Circuit Breaker, ThermMagn, 60A, 3P, 600V, 14kA

Product availability : Stock - Normally stocked in distribution facility



Price\* : 1124.00 USD



### Main

|                           |                  |
|---------------------------|------------------|
| Product or component type | Circuit breaker  |
| Range of product          | PowerPact H      |
| Trip unit technology      | Thermal-magnetic |
| Breaking capacity code    | D                |

### Complementary

|   |  |
|---|--|
| Line Rated Current                                  | 60 A   |
| Poles description                                   | 3P   |
| Breaking capacity                                   | 18 kA at 480 V AC<br>25 kA at 240 V AC<br>14 kA at 600 V AC<br>20 kA at 250 V DC |
| System Voltage                                      | 250 V DC<br>600 V AC   |
| [Ics] rated service short-circuit breaking capacity | 80 %   |
| Mounting mode                                       | I-Line   |
| Electrical connection                               | I-Line connection line<br>Lugs load  |
| AWG gauge   | AWG 14...AWG 3/0 (aluminium/copper)  |
| Phase connection                                    | ABC  |
| Magnetic hold current                               | 800 A  |
| Magnetic tripping current                           | 1450 A   |

### Environment

|                        |                  |
|------------------------|------------------|
| Product certifications | CE<br>IEC<br>CSA |
|------------------------|------------------|

UL listed

Ambient air temperature for operation 104 °F (40 °C)

### Ordering and shipping details

|                       |                                      |
|-----------------------|--------------------------------------|
| Category              | 01112 - HD, JD I-LINE BREAKER/SWITCH |
| Discount Schedule     | DE2                                  |
| GTIN                  | 00785901419969                       |
| Nbr. of units in pkg. | 1                                    |
| Package weight(Lbs)   | 5.46                                 |
| Returnability         | Y                                    |
| Country of origin     | MX                                   |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0832 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|