Product data sheet Characteristics

HGL36030

PowerPact H Circuit Breaker, ThermMagn, 30A, 3P, 600V, 18kA

Product availability: Stock - Normally stocked in distribution facility





Price*: 1493.00 USD



Main

TTIONIT		
Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip unit technology	Thermal-magnetic	
Breaking capacity code	G	

Complementary

Complementary		
Line Rated Current	30 A	
Poles description	3P	
Breaking capacity	65 kA at 240 V AC 35 kA at 480 V AC 18 kA at 600 V AC 20 kA at 500 V DC 20 kA at 250 V DC	
System Voltage	500 V DC 600 V AC	
[lcs] rated service short-circuit breaking capacity	80 %	
Mounting mode	Unit mount	
Electrical connection	Lugs load Lugs line	
AWG gauge	AWG 14AWG 3/0 (aluminium/copper)	
Magnetic hold current	350 A	
Magnetic tripping current	750 A	

Environmen[®]

Environment		
Product certifications	CSA	
	UL listed	
	CE	

- 1	EC
•	

Ambient air temperature for operation	104 °F (40 °C)
7 and chi an temperature for operation	104 1 (40 0)

Ordering and shipping details

Category	01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901598725
Nbr. of units in pkg.	1
Package weight(Lbs)	4.13999999999997
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

ontractaar warranty	
Warranty period	18 months